

## COMPACT BALANCE



53

equipoise

800-472-6703 www.ricelake.com m.ricelake.com

## equipoise<sup>®</sup> compact balance



## A perfect balance of features and value

Ideal for classrooms, laboratories and industrial applications. These seven-button balances allow quick access to 13 different units of measure, percentage, counting and accumulating.

A detachable enclosed weighing chamber is included in capacities below 1000 grams. Equipoise can be used with the included AC adaptor

or an on-board rechargeable battery that offers up to 40 hours of continuous operation. RS-232 output is standard on each model. RS-232 cable is optional.

## **Standard Features**

- Capacities between 300 g and 6000 g
- Internal resolution: 1/600,000
- LCD display
- Quick response
- Accumulation, counting and percentage modes
- 13 different units of measure
- Detachable enclosed weighing chamber (in capacities ≤1kg)
- Battery operation for up to 40 hours of continuous use (without backlight)
- Standard RS-232 interface for connecting to printer or PC

Shown with weighing chamber



|                         | EQ-300^  | EQ-600^ | EQ-1500                           | EQ-3000 | EQ-6000 |
|-------------------------|--|---------|-----------------------------------|---------|---------|
| Part Number             | 129410   | 129411  | 129412                            | 129413  | 132435  |
| Capacity (g)            | 300 g  | 600 g   | 1500 g                            | 3000 g  | 6000 g  |
| Resolution (g)          | 0.01 g   | 0.02g   | 0.05 g                            | 0.1 g   | 0.2g    |
| Weighing Units          | Gram, Carat, Ounce, Ounce Troy, Pound, Pennyweight, Grain, Momme, Hong Kong Tael, Singapore Tael, Taiwan, Tael, Tola |         |                                   |         |         |
| Operating Modes         | Weighing, Percent Weighing, Parts Counting, Accumulation   |         |                                   |         |         |
| Repeatability (g) (+/-) | 0.01 g   | 0.02g   | 0.05 g                            | 0.1 g   | 0.2 g   |
| Linearity (g) (+/-)     | 0.02g  | 0.04 g  | 0.1 g                             | 0.2g    | 0.4 g   |
| Stabilization Time      | 2 seconds  |         |                                   |         |         |
| Operating Temperature   | 32–104°F (0–40°C)  |         |                                   |         |         |
| Weighing Chamber        | 6.7 in x 5.7 in x 3.1 in (170 mm x 145 mm x 80 mm)   |         | N/A                               | N/A     | N/A     |
| Pan size                | 4.7 in Ø (120 mm Ø)  |         | 4.8 in x 5.6 in (122 mm x 142 mm) |         |         |
| Dimensions              | 7.1 in x 8.7 in x 3.3 in (180 mm x 220 mm x 85 mm)   |         |                                   |         |         |
| Est. Ship Weight        | 6.6lb (3kg)  |         |                                   |         |         |
| Calibration Weight (g)  | 300 g  | 600 g   | 1500 g                            | 3000 g  | 6000 g  |
| Power                   | AC adapter (12V/500mA); internal rechargeable battery (6V/1.2Ah)   |         |                                   |         |         |
| Warranty                | One-year limited warranty  |         |                                   |         |         |

^Weighing chamber

Your Rice Lake Weighing Systems distributor is:



To be the best by every measure<sup>®</sup>

230 W. Coleman St. • Rice Lake, WI 54868 • USA TEL: 715-234-9171 • FAX: 715-234-6967 • **www.ricelake.com**