# **Neonatal Scale**



APPROVALS





### **SPECIFICATIONS**

#### **POWER:**

9 VDC, provided by AC adaptor or internal rechargeable battery

#### BATTERY TYPE:

Sealed lead acid **BATTERY USE:** 

75 hours Automatic power-off can be configured from 0-20 minutes

### **STANDARD FEATURES**

- Capacity: 0-5lb x 0.05oz (0-2kg x 1g); 5-12lb x 0.1oz (2-6kg x 2g); 12-30lb x 0.2oz (6-15kg x 5g)
- Tray dimensions: 12 in x 22 in x 4-1/4 in Removeable tray with built-in measuring tape, two sided (up to 21-3/4 in x 1/8 in or 55 cm x 1/4 cm)
- Motiontrap<sup>™</sup> (movement compensation technology)
- 1 inch LCD display
- Buttons: reweigh, lb/kg, zero, on/off
- Reweigh function
- Low battery indication
- Movement compensation technology

# **OPERATING TEMPERATURE:** 50°F to 104°F (14°C to 40°C)

APPROVALS: CE

WARRANTY: Two-year limited warranty

PART #	MODEL	CAPACITY	EST. SHIP WEIGHT	PRICE
101133	610-10-2	0-5lb (0-2kg) x 0.05 oz (1g); 5-12lb (2-6kg) x 0.1 oz (2g);	25lb	Consult
101134	610-10-2	12-30 lb (6-15 kg) x 0.2 oz (5 g) includes 120V AC adaptor 0-5 lb (0-2 kg) x 0.05 oz (1 g); 5-12 lb (2-6 kg) x 0.1 oz (2 g);	25lb	Consult
OPTIONS		12-30lb (6-15kg) x 0.2oz (5g) includes 230V AC adaptor		

102084	. Four-sided clear tray with built-in measuring tape	.Consult
110995	. Stainless Steel cart (inside rail dimensions 23 in L x 16.5 in W)	.Consult



Pictured with four-sided tray option



Stainless Steel Cart

An ISO 9001 Registered Company © 2011 Rice Lake Weighing Systems 02/11 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.