

## NTEP Approved Bench Scale

- 3,000 Divisions
- 60 lb to 300 lb Capacity
- Large 2 Inch Display



| Model                          | UFM-B30  | UFM-B60           | UFM-B150         |
|--------------------------------|--|-------------------|------------------|
| Capacity                       | 60 lb / 30 kg  | 150 lb / 60 kg    | 300 lb / 150 kg  |
| Readability                    | 0.02 lb / 0.01 kg  | 0.05 lb / 0.02 kg | 0.1 lb / 0.05 kg |
| Divisions                      | 3,000  |                   |                  |
| Weighing Units / Functions     | lb / kg  |                   |                  |
| Stabilization Time (seconds)   | < 2  |                   |                  |
| Tare Range                     | To capacity by subtraction   |                   |                  |
| Power Source                   | Built-in rechargeable battery or external power adapter (included) |                   |                  |
| Construction                   | Stainless steel platform and cast aluminum base                    |                   |                  |
| Display                        | 2 inch / 50.8 mm, 7 segment, wide viewing angle LCD                |                   |                  |
| Platform Size (W x D x H)      | 13 x 17.7 x 3.5 inches / 330 x 450 x 90 mm                         |                   |                  |
| Overall Dimensions (W x D x H) | 13 x 20.7 x 28.3 inches / 330 x 525 x 720 mm                       |                   |                  |
| Operating Environment          | 32° ~ 104° F non condensing R.H. ≤ 95%                             |                   |                  |
| Net Weight                     | 24.2 lb / 11 kg  |                   |                  |
| Shipping Weight                | 28.6 lb / 13 kg  |                   |                  |
| IP Ratings / Approvals         | NTEP CoC # 04-100  |                   |                  |
| Options                        | RS232 Configurable printer or computer interface, EL backlight     |                   |                  |

### UFM-B Series



### Features

- Overload and shock protection mechanism
- Heavy duty rugged construction
- Low profile, compact size
- Large LCD display with wide viewing angle
- Display reads in lb and kg
- Built-in rechargeable battery or external power adapter
- Accumulation function
- Zero tracking
- Automatic power save
- Low battery indicator / charge status indicator
- Auto calibration function
- Gravitational correction software
- Adjustable feet and spirit level
- Digital motion filtering
- Optional automatic tare
- In use cover (for indicator)

### Benefits

- Protects against excessive loads and shock applied to platform
- Will withstand harsh industrial operation
- Space saving, easy to load and unload
- Easy to see weight values from a distance, reduces mistakes
- Flexibility of operation
- Portability. Battery operation minimum 100 hours (without backlight)
- Allows you to add together consecutive weights to arrive at a total
- Ensures that you always start weighing at zero
- Conserves battery power
- Alerts you to charge the battery, saving downtime
- Ensures accuracy
- Enables you to input different G acceleration factors
- Scale remains level for accurate results on uneven working surfaces - Anti-slip
- Enables animal weighing or can compensate for harsh environmental conditions
- Enables you to disregard the first item placed on the platform
- Protects indicator from damage and dirt