SB-1150 Summit™

Bariatric Wheelchair Scale



Standard Features

- · Heavy-duty mild steel construction
- Single ramp
- · Large 1 in LCD display
- · Unit of measure toggle or locking
- Motiontrap[™] movement compensation technology
- EHR capable
- USB or Bluetooth® BLE 4.0 available, part number selectable
- Tare function
- Hold function
- BMI (body mass index) function
- Factory calibrated
- 10 ft cable between scale base and display

Part Number/Price

Part #	Model #	Capacity	Price
150706	SB-1150	1,000 lb x 0.2 lb (450 kg x 0.1 kg) with USB	Consult
205977	SB-1150BLE	1,000 lb x 0.2 lb (450 kg x 0.1 kg) with Bluetooth® BLE 4.0	Consult

Shipping Weight

Part #	Model #	L (in)	W (in)	H (in)	Package Wgt. (lb)	Dim Wgt. (lb)	Shipping Wgt. (lb)
150706	SB-1150	49	48	24	363	407	407
205977	SB-1150BLE	49	48	24	363	407	407

Options/Accessories

Part #	Description	Price
133077 [†]	9 VDC adaptor, 120 V/230 V auto switching	Consult
102508 **	9 VDC adaptor, 230 V	Consult
81076	Epson TM-U220 tape printer	Consult
186830	Printer cable, 25-pin D-Sub male to RJ-45, 6 ft	Consult





Specifications

Capacity: 1,000 lb x 0.2 lb (450 kg x 0.1 kg)

Platform Dimensions:

(W x L x H) 36 in x 36 in x 4 in

Ramp Dimensions:

(W x L x H) 36 in x 28.5 in x 4 in

5-digit LCD display, 0.75 in (1.9 mm) digit height

9 VDC, provided by six AA alkaline batteries (included) or AC adaptor (optional)

Battery Type:

Six AA alkaline (included)

Battery Use:

25 hours continuous use with batteries Automatic power-off can be configured

Operating Temperature:

50° F to 104° F (14° C to 40° C)

Warranty:


Two-year limited warranty

Approvals:

APPROVALS

pending

c-Met (pending)



Dimensions

	Inches	Centimeters
Α	36.0	91.4
В	36.0	91.4
С	28.5	72.4
D	36.0	91.4
Е	4.0	10.2
F	1.0	2.5