

Intell-Check™ / Intell-Count™ Scale

- All-in-One Program – Weighing, Checkweighing (Weight / Quantity), Counting
- Programmable HI-OK-LO Audio Output
- 24 Bit Delta-Sigma A/D Converter
- 60,000 Displayed Divisions
- Internal Rechargeable Battery
- Selectable Weighing Units (g, lb, lb:oz)
- RS 232 Configurable Interface
- HI-LO-GO Light Tower



Model	SEK-6K	SEK-30K	SEK-60K
Capacity	13.2 lb / 6000 g	66 lb / 30 kg	132 lb / 60 kg
Readability	0.01 oz / 0.1 g	0.02 oz / 0.5 g	0.1 oz / 1 g
Displayed Divisions	1/60,000, 1/30,000 or 1/15,000		
Internal Counting Resolution	1,000,000		
Weighing Units / Functions	lb, lb:oz, g / counting		
Stabilization Time (seconds)	< 3		
Tare Range	To capacity by subtraction		
Maximum Zero Range	2% of rated capacity		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel pan and ABS housing		
Display	1" / 25 mm wide viewing angle backlit LCD		
Pan Size (W x D)	13.6 x 9 inches / 345 x 230 mm		
Connectivity	RS 232 interface		
Dimensions (W x D x H)	14.2 x 14.2 x 4.5 inches / 360 x 360 x 114 mm		
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%		
Net Weight	13 lb / 5.9 kg		
Shipping Weight	17 lb / 7.8 kg		

Features

HI-OK-LO Check status indicator / Programmable audio output
 Zero tracking
 Digital motion filter at zero & weighing

 Auto-calibration function
 RS 232 interface

 Easy to use keyboard arrangement

 100% subtractive tare
 Large, bright backlit display

 Adjustable feet / spirit level

 Internal rechargeable battery

 Tri-color light tower
 Low battery indicator / Charge status indicator
 Smart power saving

Benefits

Ideal for portion control, checkweighing or counting – ensures fast throughput with fewer mistakes
 Ensures that you always start weighing at zero
 Automatically adjusts for adverse environmental conditions
 Ensures accuracy
 Allows communication with peripheral data collection and printing instruments
 Makes training and operation simple, reducing mistakes
 Enables the weight of containers to be ignored
 Easy to read in all lighting conditions including bright sunlight
 The scale remains level for accurate results even on uneven working surfaces
 Portability – can be used in various locations without access to a wall outlet (battery life—approximately 90 hours – light tower requires 120 VAC)
 Easy to view by operator or supervisory staff
 Alerts you to charge the battery, saving downtime
 Conserves battery power