

75lb x0.005lb
150lb x0.01lb
300lb x0.02lb
750lb x0.05lb



- Will Drive 10 x 350 ohm or 20 x 700 ohm Load Cells
- Alibi Memory Stores 130,000+ Transactions
- 60,000 Displayed Divisions Performance
- Full Numeric & Functions Keyboard
- Counting Resolution 1.2 million
- Management Capabilities
- Multiple Data Collection
- Optional Wheel Kit
- Tri-Color Display
- Real Time Clock
- 100 PLU's





Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

PSCII
Series

Model	PSCII-AB-75	PSCII-AB-150	PSCII-AB-300	PSCII-AF-150	PSCII-AF-300	PSCII-AF-750	PSCII-AL-300	PSCII-AL-750
Capacity	75 lb	150 lb	300 lb	150 lb	300 lb	750 lb	300 lb	750 lb
Readability	lb	lb	lb	lb	lb	lb	lb	lb
Divisions	30,000							
Weighing Units	lb, kg							
Functions	Counting, Statistics, Accumulation, Data Management							
Repeatability & Linearity	+ / - one division							
Tare Range	To capacity by subtraction							
Power Source	Built-in rechargeable battery or external power adapter (included)							
Indicator Construction	ABS							
Platform Construction	Stainless steel platform cover, cast aluminum base							
Display	Tri-color backlit LCD display							
Connectivity	RS 232 Male & Female interfaces, 25 Pin relay port External input port							
Platform Size (W x D x H)	13 x 17.7 x 3.5 in 330 x 450 x 89 mm			16.5 x 20.5 x 4.5 in 420 x 520 x 120 mm			19.7 x 23.6 x 4.5 in 500 x 600 x 120 mm	
Overall Dimensions (W x D x H)	13 x 20.7 x 28.3 in 330 x 450 x 720 mm			16.5 x 23.5 x 33.9 in 420 x 520 x 860 mm			19.7 x 25.5 x 33.9 in 500 x 647 x 860 mm	
Temperature Range	10° ~ 40° C non condensing R.H. ≤ 85%							
Net Weight	25.8 lb / 11.7 kg			42.2 lb / 19.2 kg			56 lb / 25.4 kg	
Shipping Weight	29 lb / 13.2 kg			46 lb / 20.8 kg			63 lb / 28.4 kg	
Options	Ticket Printer, Label Printer, Wheel Kit							

Features

- Supports Single, Dual Range & Dual Interval operations
- All Current Operation Results Output in Database Format for Data Management, Processing & Analysis
- 100 x PLU's per Each Platform (P1, P2 & P1+P2 Together)
- Configurable Keypad, Check & System Buzzer
- Real Time Clock
- Alibi Memory to Store 130,000 Plus Transactions
- Counting Resolution / Platform- 1.2 Million
- Manual, Preset, Repetitive & Continuous Tare Operation
- Continuous Tare with Configurable Delay Time Before Tare Action
- Full Numeric & Functions Keyboard
- Multi Search Criteria for Report Generation
- Selectable Portrait / Landscape Ticket Printout Format
- Customer & Product Code & Description Support Numbers, Alphabets & Selected Symbols
- User Programmable and 10 x built-in Predefined Continuous / Interval Output Protocol
- Check Result Control for Accumulation, Data Printout & Data Output
- Supports Product Expiry Duration Input & Output
- Machine ID, Machine Group & Operator Number
- Daily, Monthly, Specific Period Report Output
- Supports Customer & Product Code & Description Input
- Supports Inquiry, Setting & Execution Commands from a PC
- 10 x Quick PLU's for Unit Weight, Quantity Check Limits, Weight Check Limits, Pre-Set Tare, Customer & Product Code Description