

- Rechargeable Battery
- Accumulation





g/ozt ct/lb..



VFS Series

Model	VFS-132	VFS-330	VFS-660
Capacity	132 lb / 60 kg	330 lb / 150 kg	660 lb / 300 kg
Readability	0.01 kg / 0.02 lb / 0.5 oz	0.02 kg / 0.05 lb / 1 oz	0.05 kg / 0.1 lb / 2 oz
Divisions	6,000	7,500	6,000
Weighing Units / Functions	kg, lb, lb:oz		
Stabilization Time (seconds)	< 1.5		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel platform, pillar, indicator and housing (Aluminum load receiving structure)		
Display	2 inch / 51 mm wide viewing angle LCD		
Platform Size (w x h x d)	16.7 x 4.7 x 20.7 inches / 425 x 120 x 525 mm		
Dimensions (w x h x d)	16.7 x 36.8 x 20.7 inches / 425 x 935 x 525 mm		
Operating Environment	32° ~ 104° F non condensing R.H. ≤85%		
Net Weight	48.4 lb / 22 kg		
Shipping Weight	50.6 lb / 23 kg		
NEMA / IP Rating	NEMA 4X / IP 65		
Options	Stainless Steel Wheel Kit, Bi-Directional RS232 Interface		

Features	Benefits	
All stainless steel housing and pan	Easy to clean for food processing or harsh environments	
Heavy duty construction	Will withstand harsh industrial operation	
Sealed electronics. Waterproof tactile keypad	Improved water and dust resistance, spraydown capable	
Large LCD display with wide angle viewing	Easy to see weight values from a distance, reduces mistakes	
Expendable pillar (another 5.5 inches / 140 mm)	Enables bulky objects to be weighed	
Reads in kilograms, pounds and pounds : ounces	Flexibility of operation	
Built-in rechargeable battery or external power adapter	Portability - battery lasts a minimum of 100 hours (without back light)	
Accumulation function	Allows you to add together consecutive weights to arrive at a total	
Zero tracking	Assures that you always start weighing at zero	
Automatic power save	Conserves battery power	
Low battery indicator	Alerts you to charge the battery, saving downtime	
Auto-calibration function	Ensures accuracy	
Adjustable stainless steel feet with rubber inserts	Scale remains level for accurate results on uneven working surfaces - anti-slip	