NEW Ready-n-Weigh Bench Scale System CW-90B Bench Scale and 380 Indicator Package

BATTERY

POWERED

drage

Standard Features

- Package includes scale with IP67 aluminum environmentally sealed load cell with an indicator and 12-inch column
- Factory calibrated, with indicator setup and configured for 5,000 divisions
- · Scale includes rubber feet to provide exceptional traction and avoid scratching surfaces along with removable top cover for ease of cleaning
- Standard RS-232 serial port for connecting to a variety of peripherals
- Powered by 4 alkaline C-cell batteries (not included) or external AC adaptor (not included)

CW-90B Specifications

- Load Cell, NTEP Certified: IP67 aluminum, environmentally sealed
- **Scale Construction:** 304 stainless steel

Maximum Overload:

180% to 200% depending on capacity

Overload Protection: Five-point, independently adjusted

Scale Frame: AISI304L, straight line finish, Ra = 45 +/- 10

Scale Cover: AISI304L, straight line finish, Ra = 45 +/- 10

Cable Length:

34 in

Compensated Temperature Range: 14° F to 104° F (-10° C to 40° C)

Approvals:

NTEP CC 95-072, Class III 5,000 d Measurement Canada AM-5082, Class III 5,000 d Load cell is cFMus Approved

Warranty: Two-year limited warranty

380 Specifications:

Power:

Batteries: 4 Alkaline C-cell Optional: 115/230 VAC to 12 VDC adapter

Battery Life: 100 hours on Alkaline batteries with one 350 ohm load cell, no backlight

Communication Ports:

One RS-232 (three-wire) One USB 2.0

Display: Six 1 in (25 mm) tall, LCD digits

Status Annunciators:

g, lb, t, tn, kg, oz, battery level, PT, LT, gross, zero, unstable, net

Keys/Buttons: 5 tactile buttons


Rating/Material:


Enclosure: IP66, 304 Stainless steel

Approvals: NTEP CC 12-123

Measurement Canada AM-5892 **CE Marked** UL/cUL Listed

Dr	Drawing Dimensions								
10	10 in x 10 in								
А	19.68 in (500 mm)	E	9.43 in (239.6 mm)						
В	10.20 in (259.1 mm)	F	4.25 in (108 mm)						
С	14.02 in (356.1 mm)	G	10.20 in (259.1 mm)						
D	13.36 in (339.3 mm)								
12 in x 12 in									
А	19.56 in (496.9 mm)	E	9.30 in (236.3 mm)						
В	12.38 in (313.8 mm)	F	4.25 in (108 mm)						
С	16.10 in (408.9 mm)	G	12.35 in (313.8 mm)						
D	13.23 in (336.1 mm)								







CW-90B with 380 indicator

RICE LAKE



APPROVALS





CW-90B with 380 Package

Part #	Capacity	Dimensions	Est. Weight	Price
208528	5 lb (2.5 kg)	10 x 10 x 4.25 in	24lb	Consult
208529	10 lb (5 kg)	10 x 10 x 4.25 in	24lb	Consult
208530	25 lb (10 kg)	10 x 10 x 4.25 in	24lb	Consult
208531	25 lb (10 kg)	12 x 12 x 4.25 in	27 lb	Consult
208532	50 lb (25 kg)	12 x 12 x 4.25 in	27 lb	Consult
208533	100 lb (50 kg)	12 x 12 x 4.25 in	27 lb	Consult

(o o) [#] Euro Plug - Type E

Options/Accessories

⁺ US plug (NA) - Type B

Part #	Description	Price
206433	External AC Adaptor	Consult
204258	Real-time clock module	Consult