


BenchMark® CW-80B

Light-capacity Bench Scale



Standard Features

- 304 stainless steel construction
- LifeGuard™ base design isolates load cell from overloads and shock loads for added durability
- Specially designed adjustable support feet provide exceptional traction and won't scratch surfaces
- NTEP Certified, IP67 stainless steel load cell

Specifications

Load Cell, NTEP Certified:

IP67 stainless steel and environmentally sealed

Output Impedance:

350 ohm

Maximum Overload:

200%

Overload Protection:

Shock-absorbing spider

Scale Frame:

AISI304L, straight line finish, Ra=45 +/- 10

Scale Cover:

AISI304L, straight line finish, Ra=45 +/- 10

Cable Length:

10 ft (3 m)

Compensated Temperature Range:

14° F to 104° F (-10° C to 40° C)

Warranty:

Two-year limited warranty

Approvals:

NTEP CC 96-107, Class III, 3000 d

Measurement Canada AM-5156, Class III 3,000 d

Load cell is FM approved

APPROVALS



BenchMark® CW-80B

Light-capacity Bench Scale

Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
35075	6 lb (3 kg)	10 x 10 x 3.15 in	13 lb	Consult
35076	10 lb (5 kg)	10 x 10 x 3.15 in	13 lb	Consult
35077	15 lb (7 kg)	10 x 10 x 3.15 in	13 lb	Consult
35078	30 lb (15 kg)	10 x 10 x 3.15 in	13 lb	Consult
35079	30 lb (15 kg)	12 x 12 x 3.25 in	14 lb	Consult
35080	60 lb (30 kg)	12 x 12 x 3.25 in	14 lb	Consult

Options/Accessories

Part #	Description	Catalog Page #
Consult	Scale Columns	See page 230
Consult	Ball Transfer and Roller Conveyor Scale Tops	See page 229
Consult	Mobile Scale Carts	See page 225 to page 228

Dimensions

Part#	Capacity	Platform Size (L x W)	L1/W1	H
35075	6 lb (3 kg)	10 x 10 in	10.25 in	3.15 in
35076	10 lb (5 kg)	10 x 10 in	10.25 in	3.15 in
35077	15 lb (7 kg)	10 x 10 in	10.25 in	3.15 in
35078	30 lb (15 kg)	10 x 10 in	10.25 in	3.15 in
35079	30 lb (15 kg)	12 x 12 in	12.25 in	3.25 in
35080	60 lb (30 kg)	12 x 12 in	12.25 in	3.25 in

Note: 1 in=25.4 mm

